

INNOVATION. PRECISION. TRUST.



YUCHAI GENSET ENGINE


2005KW

EU Stage III

20 cylinders

D2500V3-CR-TA-2065

The D2500V3-CR-TA-2065 is a high-performance 20-cylinder diesel engine delivering 1800 kW of prime power output. With a 65.3L displacement and advanced engineering, this engine provides reliable power for diverse applications.



Main technical parameters

Number of cylinders	20
Configuration	V, 90°
Aspiration	Turbocharged air-air intercooled
Combustion system	Direct injection
Compression ratio	13.5:1
Bore × Stroke	152x 180
Displacement	65.3L
Rotation	Counterclockwise (viewed from the flywheel end)
Fuel system	Electronic Pump Units
Governor	ECU
Stability at constant load (ISO 8528-5 Class G3)	± +/- 0.5 %
50/60Hz switchable operation	YES
Electric system	24V
Tropical Radiator mounted on the engine	Ambient 50°C
Flywheel Housing	SAE00 /21"
Lubrication Oil capacity	330L
Coolant capacity	619L
Emission class	EU Stage III

YUCHAIMOTOR.COM

The engine performance

Gross Engine Output 50Hz

PRP	2005 kWm
ESP	2206 kWm

Typical Generator Output 50Hz

PRP	1800 kWe
PRP	2250 kVA
ESP	2500 kVA

Fuel consumption

STANDBY(ESP)	201.3 g/kWh	531.8 L/h
PRIME(PRP)	191.8 g/kWh	460.6 L/h
75% PRP (prime)	192.2 g/kWh	346.3 L/h
50% PRP (prime)	196 g/kWh	237.5 L/h
HVO synthetic fuel acceptance		

Key Features

Main Features

- ✓ Compact design
- ✓ Good power density
- ✓ Good load acceptance
- ✓ Durability
- ✓ Easy service & maintenance
- ✓ Low fuel consumption
- ✓ Wide selection of optional equipment
- ✓ Low noise
- ✓ Tailored cooling pack (optional)

Standard scope of supply

- ✓ Cast iron cylinder block c/w separate cast iron cylinder heads
- ✓ Aluminum alloy pistons with gallery oil cooling
- ✓ Automatic belt tensioner, Lift eyes, Fixed front & rear suspension
- ✓ Radiator with mechanical pusher fan, thermostatically controlled (optional)
- ✓ Large capacity oil pan, spin-on full-flow oil filter, oil dipstick
- ✓ Electronic Pump Units fuel system
- ✓ ECU management/monitoring
- ✓ Duplex fine fuel filters
- ✓ Rear mounted turbochargers
- ✓ Top/Side mounted air filters with restriction indicator
- ✓ 24V DC electric system with two starters 11kW each
- ✓ 55A charging alternator
- ✓ Heat isolated exhaust manifold

Dimensions & Weight

Dimensions & Weight

Including radiator (dry weight)

5500

Length (mm)

2500


Width (mm)

2500

Height (mm)

14200

Weight (kg)



POWER DEFINITIONS:

ESP = STANDBY POWER

According to ISO8528 is maximum power available during variable electrical power sequence up to 200h of operation per year, permissible output over 24h operation should not exceed 70% ESP

PRP = PRIME POWER

According to ISO8528 is maximum power engine can deliver continuously for unlimited number of hours per year permissible output over 24h operation should not exceed 70% PRP

YUCHAIMOTOR.COM

**INTERNATIONAL
WARRANTY**

Prime Power
2 years with
no hours limitations
Standby Power
4 years or max. 1000 hrs
but not more than 300 hrs per year